




K 250 STATIC



LW-K



GENERAL FEATURES

- Wall fixing or stationary use configuration
- Sturdy stainless steel casing
- Easy maintenance by simply removing the casing
- Low-pressure detergent suction
- Pressure gauge
- 4-pole motor (1400 rpm) well oversized and protected with paint
- Built-in professional unloader valve
- **TotalStop**
- Self-priming pumps with **EASY-START** device on single-phase models
- Rotary switch
- Motor thermal protection



CARATTERISTICHE GENERALI

- Configurazione per fissaggio a muro o per utilizzo stazionario
- Robuste carenatura in acciaio inossidabile
- Facile manutenzione con la semplice rimozione della carenatura
- Aspirazione detergente in bassa pressione
- Manometro di pressione
- Motore a 4 poli (1400 giri/min) ampiamente sovradimensionato e protetto da verniciatura
- Valvola di regolazione professionale integrata
- **TotalStop**
- Pompe autoadescanti con dispositivo **EASY-START** per modello monofase
- Interruttore rotativo
- Protezione termica motore
- Uso professionale

ON THE WALL › A PARETE

Dual use
Doppio uso

ON THE FLOOR › A TERRA



CODE CODICE	MODELS MODELLI	PUMP POMPA										
			Ph	V	Hz	bar	MPa	l/h	HP	kW	kg	(L x W x H) cm
9057 2001	K 250 Static 10/150 M	LW-K	1	230	50	150	15	600	3,0	2,9	40	55 x 35 x 35
9057 2003	K 250 Static 12/130 M	LW-K	1	230	50	130	13	720	3,0	2,9	40	55 x 35 x 35
9057 2002	K 250 Static 15/170 T	LW-K	3	400	50	170	17	900	5,5	5,0	40	55 x 35 x 35

STANDARD ACCESSORIES › DOTAZIONE STANDARD

	GH 301 gun with swivel Pistola GH 301 con swivel		15° spray nozzle, 1/4" MEG connection Ugello con getto a lama 15° attacco 1/4" MEG
	Bent lance with detergent head, without nozzle Lancia angolata con testina detergente, senza ugello		10 m delivery hose kit with quick coupler M22x1,5 10 m rubber delivery hose kit
		Ejector kit Kit eiettore	